

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Marine Diesel Fuel Additive  
Product group : Blend

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
For professional use only  
Use of the substance/mixture : Diesel bug killer and engine performance enhancer.

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Wessex Chemical Factors Ltd  
17 Crane Way, Woolsbridge Industrial Park,  
Three Legged Cross, Wimborne, Dorset – BH21 6FA  
United Kingdom  
T +44 (0) 1202 823 699 - F +44 (0) 1202 813 863  
[www.wessexchemicalfactors.co.uk](http://www.wessexchemicalfactors.co.uk)

E-mail address of competent person responsible for the SDS : [info@wessexchemicalfactors.co.uk](mailto:info@wessexchemicalfactors.co.uk)

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 1202 823 699 (Office hours only 9am - 5pm Monday - Thursday, 9am - 4pm Friday.)  
+44 (0) 7973629367 (Out of hours emergency number)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 2	H341
Carcinogenicity, Category 1B	H350
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Causes damage to organs through prolonged or repeated exposure. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS08

Signal word (CLP)

: Danger

Contains

: Solvent naphtha (petroleum), heavy arom.; Kerosine— unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165 °C to 290 °C (330 °F to 554 °F).], Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, reaction products of paraformaldehyde and 2-hydroxypropylamine (ratio 3:2) [MBO]

Hazard statements (CLP)

: H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H341 - Suspected of causing genetic defects.

H350 - May cause cancer.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing vapours, spray, fume.

P264 - Wash hands thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P405 - Store locked up.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH044 - Risk of explosion if heated under confinement.

EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: - EC-No.: 918-481-9 REACH-no: 01-2119457273-39-0000	5 – 30	Asp. Tox. 1, H304
2- Ethylhexyl Nitrate	CAS-No.: 27247-96-7 EC-No.: 248-363-6 REACH-no: 01-2119539586-27	3 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 2, H411
2-Ethyl Hexanol	CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289-20-0000	0.1 – 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Solvent naphtha (petroleum), heavy arom.; Kerosine— unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165 °C to 290 °C (330 °F to 554 °F).]	CAS-No.: 64742-94-5 EC-No.: 265-198-5 EC Index-No.: 649-424-00-3 REACH-no: 01-2119510128-50-0000	0.1 – 5	Asp. Tox. 1, H304
reaction products of paraformaldehyde and 2-hydroxypropylamine (ratio 3:2) [MBO]	CAS-No.: 66204-44-2	0.1 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Muta. 2, H341 Carc. 1B, H350 STOT RE 2, H373 Aquatic Chronic 2, H411
1,2,4-trimethylbenzene	CAS-No.: 95-63-6 EC-No.: 202-436-9 EC Index-No.: 601-043-00-3 REACH-no: 01-2119472135-42-0000	< 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
naphthalene	CAS-No.: 91-20-3 EC-No.: 202-049-5 EC Index-No.: 601-052-00-2 REACH-no: 01-2119561346-37-0000	< 1	Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general

: Call a physician immediately. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after skin contact	: If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a physician immediately. Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Suspected of causing genetic defects. May cause cancer.
Symptoms/effects after inhalation	: Possible respiratory damage following repeated or prolonged inhalation. Irritation of the respiratory tract. May cause an allergic skin reaction.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema. Small amounts of liquid aspirated into the respiratory system during ingestion/vomiting may cause bronchopneumonia or pulmonary oedema. May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Use of heavy stream of water may spread fire. Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Will ignite if exposed to intensive heat.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Risk of explosion if heated under confinement.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Spilled material may present a slipping hazard. Remove ignition sources. No open flames. No smoking. Use special care to avoid static electric charges.
------------------	---

#### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Evacuate unnecessary personnel.
----------------------	---

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13. See Section 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : All containers must be labelled to warn against exposure. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe mist, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray. Obtain special instructions before use. Use personal protective equipment as required. Do not handle until all safety precautions have been read and understood. Keep away from sources of ignition - No smoking. No open flames. No smoking.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always wash hands after handling the product. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Store locked up. Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.
- Incompatible products : Strong oxidizing agents. Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

2-Ethyl Hexanol (104-76-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-ethylhexan-1-ol
IOEL TWA	5.4 mg/m <sup>3</sup>
IOEL TWA [ppm]	1 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
United Kingdom - Occupational Exposure Limits	
Local name	2-ethylhexan-1-ol

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-Ethyl Hexanol (104-76-7)	
WEL TWA (OEL TWA) [1]	5.4 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	1 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

1,2,4-trimethylbenzene (95-63-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	1,2,4-Trimethylbenzene
IOEL TWA	100 mg/m <sup>3</sup>
IOEL TWA [ppm]	20 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

naphthalene (91-20-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Naphthalene
IOEL TWA	50 mg/m <sup>3</sup>
IOEL TWA [ppm]	10 ppm
Remark	(Year of adoption 2010)
Regulatory reference	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Safety glasses. Gloves. Avoid all unnecessary exposure.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Chemical goggles or safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Hand protection:

Wear protective gloves.

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection.

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 320 °C
Flash point	: ~ 74 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: The product is not easily ignited, Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: ~ 19.5 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available
Explosive properties	: No direct explosion hazard. Risk of explosion if heated under confinement.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: The product is a complex mixture, the majority of which would not be classed as a VOC, however trace or low levels may be present.
-------------	--

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions. Risk of explosion if heated under confinement. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon oxides (CO, CO<sub>2</sub>). fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### 2-Ethyl Hexanol (104-76-7)

LD50 oral rat	2047 mg/kg bodyweight
---------------	-----------------------

**Solvent naphtha (petroleum), heavy arom.; Kerosine— unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165 °C to 290 °C (330 °F to 554 °F).] (64742-94-5)**

LD50 oral rat	> 5000 mg/kg bodyweight
---------------	-------------------------

LD50 dermal rabbit	> 2000 mg/kg bodyweight
--------------------	-------------------------

LC50 Inhalation - Rat	> 6.03 mg/l/4h
-----------------------	----------------

#### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (-

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
-----------------	--

LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
--------------------	---

#### reaction products of paraformaldehyde and 2-hydroxypropylamine (ratio 3:2) [MBO] (66204-44-2)

LD50 oral rat	632 mg/kg
---------------	-----------

LD50 dermal rat	760 – 6000 mg/kg
-----------------	------------------

LC50 Inhalation - Rat (Dust/Mist)	2 mg/l/4h
-----------------------------------	-----------

Skin corrosion/irritation : Causes skin irritation.  
Additional information : Repeated exposure may cause skin dryness or cracking.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Suspected of causing genetic defects.  
Carcinogenicity : May cause cancer.  
Reproductive toxicity : Not classified  
Additional information : Based on available data, the classification criteria are not met  
STOT-single exposure : Not classified  
Additional information : Based on available data, the classification criteria are not met

#### 1,2,4-trimethylbenzene (95-63-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------



# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-repeated exposure : Not classified  
Additional information : Based on available data, the classification criteria are not met

### reaction products of paraformaldehyde and 2-hydroxypropylamine (ratio 3:2) [MBO] (66204-44-2)

STOT-repeated exposure	May cause damage to organs (gastro-intestinal tract, respiratory tract) through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : May be fatal if swallowed and enters airways.

### Marine Diesel Fuel Additive

Viscosity, kinematic	~ 19.5 mm <sup>2</sup> /s
----------------------	---------------------------

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.  
Ecology - water : Harmful to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

### 2- Ethylhexyl Nitrate (27247-96-7)

LC50 - Fish [1]	2 mg/l Zebrafish (Danio rerio)
EC50 - Crustacea [1]	> 12.6 mg/l
EC50 72h - Algae [1]	1.57 mg/l
ErC50 algae	3.22 mg/l

### 1,2,4-trimethylbenzene (95-63-6)

LC50 - Fish [1]	7.72 mg/l Fathead Minnows (Pimephales promelas)
EC50 - Crustacea [1]	3.6 mg/l
ErC50 algae	2.356 mg/l

### naphthalene (91-20-3)

LC50 - Fish [1]	0.9 mg/l
EC50 - Crustacea [1]	2.16 mg/l
EC50 72h - Algae [1]	2.96 mg/l

**Solvent naphtha (petroleum), heavy arom.; Kerosine— unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165 °C to 290 °C (330 °F to 554 °F).] (64742-94-5)**

LC50 - Fish [1]	2 – 5 mg/l
EC50 - Crustacea [1]	1.4 mg/l
EC50 72h - Algae [1]	1 – 3 mg/l
NOEC chronic fish	0.098 mg/l

### reaction products of paraformaldehyde and 2-hydroxypropylamine (ratio 3:2) [MBO] (66204-44-2)

LC50 - Fish [1]	71 mg/l
EC50 - Crustacea [1]	29 mg/l

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### reaction products of paraformaldehyde and 2-hydroxypropylamine (ratio 3:2) [MBO] (66204-44-2)

ErC50 algae	2.95 mg/l
-------------	-----------

### 12.2. Persistence and degradability

#### Marine Diesel Fuel Additive

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

#### 2-Ethyl Hexanol (104-76-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

### 12.3. Bioaccumulative potential

#### Marine Diesel Fuel Additive

Bioaccumulative potential	Due to the consistency along with the low water solubility of the product a bioavailability is unlikely. Not established.
---------------------------	---

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Hazardous waste due to potential risk of explosion.
Ecology - waste materials	: Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

#### Rail transport

Not regulated

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Substances subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer: Tetrachlorodifluoroethane (-).

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : The product is a complex mixture, the majority of which would not be classed as a VOC, however trace or low levels may be present.

Contains substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
-----	---

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
EC50	Median effective concentration
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
vPvB	Very Persistent and Very Bioaccumulative

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.

# Marine Diesel Fuel Additive

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.