

WP 1400

GLUE REMOVER

Alcohol based, low-toxicity glue remover which can even be used in confined spaces



BENEFITS

- Removes a variety of different glues.
- Causes less headaches when compared with other glue removers.
- Stays wet to aid the removal of glue, before evaporating clear.
- Low toxicity
- Safe on painted, plastic and styrene surfaces.

DESCRIPTION

Our solvent blend Glue Remover has been designed to stay wet long enough to make it easy to wipe off glue (various types), before the product evaporates.

Alcohol based formula causes less headaches than products containing harsh solvents (such as xylene). Does not contain petroleum. No overpowering odours so can be used in confined spaces without problems.

Glue removal from a variety of surfaces not harmed by water.

Flammable product, but fully biodegradable.

PRODUCT SIZES

- 5 litres

INSTRUCTIONS FOR USE

Spray Glue Remover onto adhesive residue. Leave for a few seconds and then remove with a cloth or paper towel.

Repeat if necessary.

HEALTH & SAFETY

Hazard pictograms (CLP):



Hazard statements (CLP):

H226 – Flammable liquid and vapour.

H304 – Maybe fatal if swallowed and enters airways.

H319 – Causes serious eye irritation.

H336 – May cause drowsiness or dizziness.

PHYSICAL PROPERTIES

Colour: Colourless.

Appearance: Mobile liquid.

Odour: No data available.

Solubility: No data available.

Boiling point: No data available.

Flash point: 24°C.

Flammability: Not applicable.

Density: 0.783 g/cm³.

pH: N/a.

Wessex Chemical Factors Ltd

17 Crane Way

Woolsbridge Industrial Park

Three Legged Cross

Wimborne

Dorset

BH21 6FA

United Kingdom

Tel: 01202 823699

Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk

Website: www.wessexboatstore.co.uk



HEALTH & SAFETY (Cont.)

Precautionary statements (CLP):

P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources > No smoking.

P233 – Keep container tightly closed.

P240 – Ground and bond container and receiving equipment.

P241 – Use explosion proof electrical equipment.

P261 – Avoid breathing vapour, spray, mist.

P264 – Wash hands thoroughly after handling.

P271 – Use only outdoors or in a well-ventilated area.

P280 – Wear eye protection, protective gloves, protective clothing.

P301+310 – IF SWALLOWED: Immediately call a doctor, a POISON CENTRE.

P303+P361+P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do. Continue rinsing.

P312- Call a doctor, a POISON CENTRE if you feel unwell.

P331 – Do NOT induce vomiting.

P337+P313 – If eye irritation persists: Get medical advice/attention.

P370+P378 – In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, Water spray, alcohol resistant foam to extinguish.

P403+P233 – Store in a well-ventilated place. Keep container tightly closed.

P403+P235 – Store in a well-ventilated place. Keep cool.

P405 – Store locked up.

P501 – Dispose of contents/containers to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH210 – Safety Data Sheet available on request.

