

WP 1601

LOW FOAM DECK WASH

Specially formulated biodegradable low foaming deck wash cleaner suitable for use in grey water tanks



BENEFITS

- One product for many applications.
- Highly concentrated.
- Cleans difficult surfaces.
- Biodegradable.
- Environmentally friendly.
- Doesn't affect grey and black water holding tanks.
- Meets Royal Navy Department of Medicine specification.

PRODUCT SIZES

- 3.25 litre

DESCRIPTION

A highly concentrated, environmentally friendly formula that uses ingredients from the cosmetic industry. When diluted the solution is very safe for users.

Designed for use with cold or warm water for difficult to clean surfaces such as safety flooring or rubber marks on fibreglass hulls. Will not dull painted surfaces even when contaminated by oil and grinding contaminants.

WARNING – May remove some teak deck sealers.

3.25 litre container will make up 250 litre of high-quality cleaning fluid.

INSTRUCTIONS FOR USE

1. Sweep the deck.
2. Add the deck wash to warm water. Dilution rate depends on the degree of staining.
3. Apply product using suitable equipment, deck scrubber or machine that has soft or medium duty pads or brushes fitted.
4. Leave deck wash on soiled area for 5 – 8 minutes to allow the product to work.
5. Rinse area with clean water, then dry area.
6. To be read in conjunction with Health and Safety guidelines below.

Dilution rate:

If not using pump dispenser:

Regular cleaning: 80:1 ratio

Approximately 12.5ml per litre of water.

Heavily soiled area: 40:1 ratio

Approximately 25ml per litre of water

If using pump dispenser:

Regular cleaning: Two pumps in 4 litres of water.

Heavily soiled: Four pumps in 4 litres of water.

PHYSICAL PROPERTIES

Colour: Colourless.

Appearance: Liquid

Odour: No data available

Solubility: Soluble in water

Boiling point: No data available.

Flash point: >65°C

Flammability: Not applicable.

Density: 1.075g/cm³

pH: 12.9 - 13.

HEALTH & SAFETY

Hazard pictograms (CLP):



Hazard statements (CLP):

H290 – May be corrosive to metals.

H318 – Causes serious eye damage.

Precautionary statements (CLP):

P234 – Keep only in original container.

P280 – Wear eye protection, protective gloves.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P310 – Immediately call a doctor, a POISON CENTRE.

P390 – Absorb spillage to avoid material damage.

P406 – Store in a corrosive resistant container with a resistant liner.

Hazardous ingredients:

C9 -11 alcohol ethoxylate with 6.5 mol EO

EUH210 – Safety Data Sheet available on request.

Wessex Chemical Factors Ltd

17 Crane Way

Woolsbridge Industrial Park

Three Legged Cross

Wimborne

Dorset

BH21 6FA

United Kingdom

Tel: 01202 823699

Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk

Website: www.wessexboatstore.co.uk

