

Mould Suppressant



A treatment chemical designed to eradicate and prevent mould & algae growth on wood, concrete, tarmac and other hard surfaces exposed to the elements.

BENEFITS

- Removes black mould spores
- Prevents regrowth of mould spores
- No hard work or scrubbing

DESCRIPTION

Mould Suppressant is a dual-purpose product which works by dislodging the black biological residues which can blight a decks appearance. Its primary use is for treating tired surfaces which are not soiled with oil or diesel but are in need of a refresh. Over several weeks it will restore the surface back to a clean appearance.

Secondly it can be used as an overwintering solution to preserve the appearance of the surface and prevent greening.

INSTRUCTIONS FOR USE

Mould Suppressant must be applied to a dry area. It is normally diluted with between 1 and 3 parts water to 1-part Mould Suppressant

Apply liberally to the area so that the surface is saturated. For best results, a second coat must be applied within a week, also on a dry day.

Once the application is complete, simply walk away and leave it. Over the course of the next few weeks you will see a marked improvement and protection from black and green marks.

By using this method, some customers have reported their patios and fences to be maintained for up to 2 years.

Please note, there will be **NO immediate visible improvement** but, over the following weeks, you will see a general lightening and cleaning of the area and a significantly improved appearance.

Mould algae and algae spots should disappear as Mould Suppressant detaches the black residues from the surface and allows the elements to wash them away.

PHYSICAL PROPERTIES

Physical state: Liquid

Appearance: Clear, colourless liquid.

Colour: Colourless.

Odour: characteristic.

Flammability (solid, gas): Non-flammable.

Density: 1.054 g/cm³

Solubility: soluble in water.

HEALTH & SAFETY

Danger

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H360 - May damage fertility or the unborn child

H412 - Harmful to aquatic life with long lasting effects

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P264 - Wash hands thoroughly after handling

P273 - Avoid release to the environment

P280 - Wear eye protection, protective gloves

P302+P352 - IF ON SKIN: Wash with plenty of water

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313 - IF exposed or concerned: Get medical advice/attention

P332+P313 - If skin irritation occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P362+P364 - Take off contaminated clothing and wash it before reuse

P405 - Store locked up

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

Hazardous ingredients: disodium octaborate

Manufactured by:

**Wessex Chemical Factors
17 Crane Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne
Dorset
BH21 6FA
United Kingdom**

Tel: 01202 823699

Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk

Website: www.wessexboatstore.co.uk



Mould Suppressant
17/6/21