WP 1214

RAPID CLEANSE

Powerful formulation cleans and preserves central heating systems



BENEFITS

- Powerful cleaner removes sludge, flux, debris & scale.
- Superb results with or without a powerflushing machine
- Effective results on NEW & OLD, HOT or COLD central heating systems.
- Restores heating efficiency, circulation and reduces boiler noise
- Suitable for all metals including aluminium.
- Non-toxic and biodegradable

DESCRIPTION

Powerflush cleaner is a total, one action cleaning solution for the quick and effective removal of sludge, flux, scale, calcium/iron deposits and other debris from an existing central heating system.

PHYSICAL PROPERTIES

Physical state: Liquid

Colour: Colourless

Odour: Characteristic

Flammability (solid, gas): Non flammable

Relative density: 1.138 g/ml

Solubility: Soluble in water

PACKAGING

1 It

5lt

INSTRUCTIONS FOR USE

1 litre of Powerflush Cleaner is sufficient to clean an average sized domestic heating system (100 litres or up to 10 radiators). Badly fouled, heavily sludged or larger systems may require more. If used in conjunction with a powerflush machine, please refer to the unit manufacturer's instructions for use.

Circulate Powerflush Cleaner, preferable at normal operating temperature, with all valves open and the pump turned to maximum flow for a minimum period of one hour or until satisfactory performance is restored. Although it is best to remove the flocculated debris, if it is not practicable to do so, Powerflush Cleaner can be left in and will at least keep the debris moving whilst the pump is on.

No neutralisation is required. Treat with Corrosion Inhibitor afterwards to protect and preserve systems.

OPEN SYSTEMS: Dose via header tank (sufficient draining from a low point is required to ensure the entire product enters the circulating part of the system).

SEALED SYSTEMS: If the system is empty, add to any convenient part before filling. If full, inject via the filling loop, or other accessible point.

HEALTH & SAFETY

Warning

H302 – Harmful if swallowed.

H319 - Causes serious eye irritation.

P264 – Wash hands thoroughly after handling.

P270 – Do not eat, drink or smoke when using this product.

P280 – Wear eye protection, protective gloves. P301+P312 – IF SWALLOWED: Call a POISON CENTRE/doctor/.../if you feel unwell.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P330 – Rinse mouth.

P337+P313 – If eye irritation persists: Get medical advice/attention.

P501- Dispose of contents/container to a licensed hazardous waste disposal contractor or collection site except for empty clean containers which can be

Wessex Chemical Factors Ltd 17 Crane Way Woolsbridge Industrial Park Three Legged Cross Wimborne Dorset BH21 6FA United Kingdom

Tel: 01202 823699 Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk Website: www.wessexchemicalfactors.co.uk



