

WP 1223

SLUDGE & FLUX REMOVER

Commissioning and maintenance cleaner for new and old central heating systems



BENEFITS

- Cleans and removes sludge, flux & installation debris
- Suitable for new (commissioning) and old (maintenance) heating systems
- Suitable for all metals including aluminium
- Non-toxic and biodegradable

DESCRIPTION

Cleans and neutralises sludge, flux, debris, oils and greases from new and old central heating systems.

Sludge & Flux Remover flocculates magnetite sludges and particulate residues, to facilitate their easy removal when flushing with or without powerflushing machine.

PHYSICAL PROPERTIES

Physical state: Liquid

Appearance: Clear, colourless liquid

Colour: Clear

Odour: Characteristic

pH: 12

Flammability (solid, gas): Non flammable

Relative density: 1.111 g/ml

Solubility: Soluble in water

INSTRUCTIONS FOR USE

Dose system at 1% i.e. 1 litre per 100 litres of system water or 10 radiators. 1 bottle should be sufficient for a typical central heating system. For larger systems an extra bottle is required. Overdosing the system does not present a problem. N.B. Where a thermal storage appliance is fitted, allow for an additional volume of primary water.

OPEN SYSTEMS: Dose via header tank (sufficient draining from a low point is required to ensure the entire product enters the circulating part of the system)

SEALED SYSTEMS: If the system is empty, add to any convenient part before filling. If full, inject via the filling loop, or other access point.

To clean an existing system, circulate product through the system with all valves open, preferably at room temperature. Leave for a minimum of 2 hours or until satisfactory performance is restored. For badly fouled systems, a longer period of circulation is recommended i.e. up to 4 weeks. Flush the system before refilling and treat with our Corrosion Inhibitor. Use also when fitting new boilers or pumps to an existing system, or where radiators have cold areas due to sludge build up.

PACKAGING

1lt

5lt

25lt

210lt

HEALTH & SAFETY

Warning

H302 – Harmful if swallowed.

P264 – Wash hands thoroughly after handling.

P270 – Do not eat, drink or smoke when using this product.

P301+P312 – IF SWALLOWED: Call a POISON CENTRE/doctor/.../if you feel unwell.

P330 – Rinse mouth.

P501- Dispose of contents/container to a licensed hazardous waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

Wessex Chemical Factors Ltd
17 Crane Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne
Dorset
BH21 6FA
United Kingdom

Tel: 01202 823699

Fax: 01202 813863

Email: info@wessexchemicalfactors.co.uk

Website: www.wessexchemicalfactors.co.uk

