

WCF 4 MAINTENANCE SPRAY

Silicone-free maintenance spray and water repellent.



BENEFITS

- Penetrating, freeing oil and release additive.
- Rapid water repellent.
- Light lubricant.
- Suitable for paintwork, rubber, plastics, textiles and metals.

PRODUCT SIZES

- 500ml aerosol can.
- 500ml aerosol cans (dozen)

DESCRIPTION

WCF4 Maintenance Spray combines dewatering and corrosion prevention in one operation. Light mist removal on mild steel and up to six months protection indoors.

'Dries out' ignition systems etc, to prevent shorting.

WCF4 Maintenance Spray frees seized nuts, bolts etc. Stops squeaks and has excellent lubricating qualities, even at sub-zero temperatures down to -20°C.

WCF4 Maintenance Spray has low toxicity after solvent evaporation. Does not normally affect paint, rubber, plastic or textiles.

Do not spray onto short circuits where sparking is likely to occur

INSTRUCTIONS FOR USE

Use aerosol spray on areas affected.

HEALTH & SAFETY

Hazard pictograms (CLP):



Hazard statements (CLP):

H222 – Extremely flammable aerosol.
H229 – Pressurised container: May burst if heated.
H315 – Causes skin irritation.
H336 – May cause drowsiness or dizziness.
H411 – Toxic to aquatic life with long lasting effects.

PHYSICAL PROPERTIES

Colour: Light brown.
Appearance: Liquid under pressure.
Odour: No data available.
Solubility: Insoluble in water.
Boiling point: No data available.
Flash point: <0°C.
Flammability: Extremely flammable aerosol.
Density: No data available.
pH: N/a.

Wessex Chemical Factors Ltd
17 Crane Way
Woolsbridge Industrial Park
Three Legged Cross
Wimborne
Dorset
BH21 6FA
United Kingdom

Tel: 01202 823699
Fax: 01202 813863
Email: info@wessexchemicalfactors.co.uk
Website: www.wessexboatstore.co.uk



HEALTH & SAFETY (Cont.)

Precautionary statements (CLP):

P102 – Keep out of reach of children.
P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 – Do not pierce or burn, even after use.
P261 – Avoid breathing vapours, spray.
P264 – Wash hands thoroughly after handling.
P271 – Use only outdoors or in a well-ventilated area.
P273 – Avoid release to the environment.
P280 – Wear protective gloves.
P302+P352 – IF ON SKIN: Wash with plenty of soap and water.
P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 – Call a doctor, call a POISON CENTRE if you feel unwell.
P332+P313 – If skin irritation occurs: Get medical advice/attention.
P362+P364 – Take off contaminated clothing and wash before reuse.
P391 – Collect spillage.
P403+P223 – Store in a well-ventilated place. Keep container tightly closed.
P405 – Store locked up.
P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 – Dispose of contents/container to hazardous or specialist waste collection point, in accordance with local, regional, national and/or international regulation.

Hazardous ingredients:

Distillates (petroleum), hydrotreated light, Kerosine - unspecified, [a complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).]

EUH210 – Safety Data Sheet available on request.

